

EE

2

-

9

02

P

T

12

CS

X

**Sling Type**  
**TC** – Type 1 – Triangle/Choker  
**TT** – Type 2 – Triangle/Triangle  
**EE**- Type 3 & 4 – Eye/Eye  
**EN** - Type 5 & 6 - Endless  
**RE** – Reverse Eye  
**WL** – Wide Lift

**Number of Plies**  
 1, 2, 3 or 4

**Web Class**  
**7** – Web 7500 – Light Duty  
**9** – Web 9800 – Heavy Duty

**Sling Width** in inches

**Web Material**  
**C**- Codura Pad  
**P**- Polyester  
**N**- Nylon  
**T**- Polyester Tuff Edge  
**E**- Nylon Tuff Edge

**Eye Treatments**  
**Flat Eyes (Type 3)**  
**F** - Standard  
**G**- Lined Bearing Point  
**H**- Fully Lined  
**I**- Wrapped Bearing Point  
**J**- Fully Wrapped  
**Twisted Eyes (Type 4)**  
**T**- Standard  
**U**- Lined Bearing Point  
**V**- Fully Lined  
**W**- Wrapped Bearing Point  
**X**- Fully Wrapped  
 Exceptions: Class 1, 2 and SH slings.  
**Tapered Eye Standards**  
**Non- Tapered:** 1” and 2” wide slings.  
**Tapered:** 3” wider and up, in class 6 & 8 slings only.  
**Note:** Other treatments can be accommodated. Please specify at time of order.

**'X'** – Special  
**'M'** – Military  
**'N'** – Not Applicable

\*Always protect webbing from being cut or damaged by corners, edges and protrusions using protection sufficient for each application.

**Web Protector**  
**CS** – Codura Slide  
**CR** – Codura Removal  
**PP** – Polyester Pad  
**PR** – Polyester Removal  
**FP** – Felt Pad  
**NA** – Not Applicable



**Sling Length**  
 Use actual pull to pull length (reach) in feet.