

SERVICE SLING

Quality, Service, and Commitment

www.servicesling.com

(713) 643-5565

ENDLESS ROUNDSLING CAPACITY CHART & ORDERING

Part Color	Color	Part Number	Vertical	Choker	Basket	60°	45°	30°	Minimum Length	Approx. Diameter	Approx. WT / FT
PURPLE	A30	ENR1P	2,600	2,100	5,200	4,500	3,700	2,600	1 ½'	1 ½"	0.3 LB
GREEN	A60	ENR2P	5,300	4,200	10,600	9,200	7,500	5,300	1 ½'	1 ¾"	0.4 LB
YELLOW	A90	ENR3P	8,400	6,700	16,800	14,500	11,900	8,400	1 ½'	2 ¼"	0.5 LB
TAN	A120	ENR4P	10,600	8,500	21,200	18,400	15,000	10,600	1 ½'	2 ¼"	0.6 LB
RED	A150	ENR5P	13,200	10,600	26,400	22,900	18,700	13,200	1 ½'	2 5/8"	0.8 LB
WHITE	A180	ENR6P	16,800	13,400	33,600	29,100	23,800	16,800	3'	2 5/8"	0.9 LB
BLUE	A240	ENR7P	21,200	17,000	42,400	36,700	30,000	21,200	3'	3 ½"	1.3 LB
ORANGE	A300	ENR8P	25,000	20,000	50,000	43,300	35,400	25,000	3'	4 5/16"	1.6 LB
GRAY	A360	ENR9P	31,000	24,800	62,000	53,700	43,800	31,000	3'	4 5/16"	2.0 LB
ORANGE	A400	ENR10P	40,000	32,000	80,000	69,300	56,600	40,000	3'	4 ¾"	2.6 LB
BROWN	A600	ENR11P	53,000	42,400	106,000	91,800	74,900	53,000	5'	5 ¾"	3.4 LB
OLIVE	A800	ENR12P	66,000	52,800	132,000	114,300	93,300	66,000	5'	5 ¾"	4.3 LB
BLACK	A1000	ENR13P	90,000	72,000	180,000	155,900	127,300	90,000	5'	5 ¾"	5.9 LB

Features:

- Double polyester tubing for better abrasion resistance, and easier inspection
- Orange vinyl tag with clear inscription of sling
- Vinyl tag sewn on a buffer sleeve or on sling per directions
- Design factor of 5 to 1
- Made in USA

How to order:

- Identify the part number you want along with the length in feet of the sling i.e. a 3' purple sling would be ENR1PX03 and then total quantity.
- Include EE (Eye to Eye), EN (Endless), or RE (Reverse Twisted).
- Add sleeve for additional protection.

GENERAL NOTES:

- Roundslings are identified by the vertical rated load shown on the sling identification. The size numbers in the first column have been adopted by the Web Sling & Tie Down Association to describe certain polyester roundslings. They are included for references only. Other polyester roundslings may have different vertical rated loads.
- Color guidelines for polyester roundslings covers are widely used to indicate the vertical rated load of roundslings; however, this is not followed by some manufacturers. Always select and use roundslings by the rated load as shown on the sling identification; never by color.
- For choker hitch, the angle of choke is 120 deg or greater.